Balmoral

Designer Light Filtering & Blackout

TEXSTYLE

Balmoral

Balmoral offers a complete styling solution with elegant colors and a premium design aesthetic. Its specialty weave creates a light modern texture and provides a subtle mix of natural colors that elevates any space. Offered in coordinating light filtering and blackout colors, you can select the level of privacy that is needed.

Features

- Luxurious designer aesthetic
- Available in 13 matching light filtering and blackout colors
- GREENGUARD Gold and OEKO-TEX Standard 100 certified
- Can be used with Roller, Roman, and Panel Track systems
- Available in a versatile 118" width
- PVC free, lead free, and phthalate free

Colors

ARMOUR	CHROME	PLATINUM	WHITE
PEARL	BIRCH	PUTTY	CONCRETE
DOVE	PYRITE	BOURNEVILLE	STEEL
JET			

Balmoral
Designer Light Filtering & Blackout

TEXSTYLE

Specifications

	Light Filtering	Blackout
Composition	100% Polyester	100% Polyester with Acrylic Foam Backing
Openness	Approximately 6%	Blackout
Weight	6.49 oz/yd² (220 g/m²)	11.50oz/yd² (390 g/m²)
Thickness	0.022 in (.55mm)	0.023in (.60mm)
Light fastness	≥ 5 (Blue Wool Scale)	
Average length	22yd/roll (20m)	
Width	118" (3m)	
Cutting	Cold Cutting or Ultrasonic Cutting	
Welding	Tape Recommended. 320-356°F (160-180°C), Test first.	
Railroadable	No	
Cleaning	Vacuum cleaning and/or gentle wiping with a sponge and mild soap. Do not soak, do not use any other solvents, and do not rub.	
Environmental Standards	GREENGUARD Gold, OEKO-TEX Standard 100, Environmental Product Declaration, REACH Compliant, RoHS Compliant	

Thermal and Optical Factors

COLOR	THERMAL FACTORS					OPTICAL FACTORS
	T_s	R_s	A_s	Single Glass Reference Glazing A [g window 0.85] [U window 5.7] g-total	High Performance Glass Reference Glazing D [g window 0.32] [U window 1.1] g-total	T_v
Blackout	0	83	17	0.23	0.23	0
White LF	46	54	0	0.46	0.26	47
Dove LF	25	34	41	0.55	0.28	21
Concrete LF	37	42	21	0.52	0.27	34
Pearl LF	46	53	1	0.47	0.27	47
Birch LF	40	48	12	0.49	0.27	39
Puffy LF	40	48	12	0.49	0.27	39
Pyrite LF	17	21	62	0.61	0.29	15
Bourneville LF	10	11	79	0.66	0.30	9
Steel LF	13	17	70	0.63	0.29	11
Jet LF	7	8	85	0.68	0.30	6

GREENGUARD GOLD — PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

EPD®

OEKO-TEX® STANDARD 100

AERC MATERIALS

5 YEAR WARRANTY

ISO 9001

FR

PHTHALATE FREE

FRAGRANCE FREE

REACH COMPLIANT

RoHS COMPLIANT

PRINTABLE